

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau




(43) International Publication Date  
6 November 2003 (06.11.2003)

PCT

(10) International Publication Number  
WO 03/090969 A1

- (51) International Patent Classification<sup>7</sup>: B23Q 16/00, 3/18, B41F 27/00
- (21) International Application Number: PCT/EP02/04848
- (22) International Filing Date: 26 April 2002 (26.04.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant (for all designated States except US): STROBBE GRAPHICS N.V. [BE/BE]; Oostkaai 50, B-8900 Ieper (BE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): WATTYN, Bart [BE/BE]; Oostkaai 50, B-8900 Ieper (BE).
- (74) Agents: OSTYN, Frans et al.; K.O.B. N.V., Kennedypark 31C, B-8500 Kortrijk (BE).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: POSITIONING DEVICE, ESPECIALLY FOR OFFSET PLATES



(57) Abstract: The invention relates to a device for positioning an element (2) with respect to at least two reference points (4a, 4c), in which said device (1) acts upon a working point on the element (2) to be positioned and comprises a positioning arm (5) attached to a fixed hinging point (7) with respect to said reference points (4a, 4c), comprising two mutually hinged parts (6a, 6b) allowing a movement of said element (2) to each reference point (4a, 4c). The invention relates further to a device for positioning at least one offset plate (2) on a positioning table (3) of a pre-press equipment, comprising means (5) to move the offset plate (2) in a plane parallel to the positioning table (3) to at least one reference point (4a) on the positioning table (3), in which said means (5) act upon a working point situated in the supporting plane of the offset plate (2) on the positioning table (3).

WO 03/090969 A1